







Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
KAMERE HDCVI 5MPX				
VND01050		<p>Dahua HAC-B1A51-U-0280B</p> <ul style="list-style-type: none"> - 5MP Bullet IC kamera, - 2.8mm F2.0 fiksni objektiv, - Smart IC diode dometa cca. 30m, - Plastično kućište, - Dimenzije 146.1mm × 70.0 mm × 69.8mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc ±30%/3,7W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 	33.00	39.60
VND01052		<p>Dahua HAC-HAC-T1A51U-0280B</p> <ul style="list-style-type: none"> - 5MP dome IC kamera, - fiksni objektiv 2.8mm F2.0, - Vidni ugao 106° H, - Smart IC diode dometa cca. 25m, - Plastično kućište, - Dimenzije Ø85.0 mm × 77.1 mm, - Radna temperatura -40°C~+55°C, - Napajanje 12VDc ±30%/2.7W, - Pripadajuće dozne PFA12C 	33.00	39.60
VND01051		<p>Dahua HAC-B2A51-U-0280B</p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F2.0 fiksni objektiv, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije 150.0 mm × 69.7 mm × 70.0 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc ±30%/3,7W, - Pripadajuće dozne PFA130-E, PFA134. 	37.00	44.40




VND01053		<p><u>Dahua HAC-T2A51-U-0280B</u></p> <ul style="list-style-type: none"> - 5MP eyeball IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 106°H, - Smart IC LE diode dometa cca. 30m, - Metalno kućište, - Dimenzije $\Phi 94.0$ mm \times 77.9 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc \pm30%/3.7W, - Pripadajuće dozne PFA13-A, PFB205W, PFA152-E, PFA106, PFB220C. 	37.00	44.40
VND01022		<p><u>Dahua HAC-HFW1500C-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 111°H, - Smart IC LE diode dometa cca. 30m, - Plastično kućište, - Dimenzije 161.3mm \times 69.7mm \times 70.0mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc \pm30%/3.7W, - Pripadajuće dozne PFA130-E, PFA134, PFA152-E. 	40.00	48.00
VND01012		<p><u>Dahua HAC-HFW1500T-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 2.8mm fiksni objekti, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije 174.5 mm \times 72.3 mm \times 70.6 mm, - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12VDc/3.2W, - Pripadajuće dozne PFA134, PFA152-E. 	65.00	78.00


VND01026		<p><u>Dahua HAC-HFW1500TL-A-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 3.6mm F1.6 fiksni objektiv, - Vidni ugao 92° H, - Smart IC LE diode dometa cca. 80m, - Integrisan mikrofon, - Kućište od metala i plastike, - Dimenzije 80.2mm × 76.2mm × 198.9mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12V ±30% DC/ 5.2W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	58.00	69.60
VND01023		<p><u>Dahua HAC-HFW1500CL-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 5MP Bullet sa hibridnim iluminatorima, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 106° H, - IC i Bele LE diode dometa 20m , - Integrisan mikrofon, - Plastično kućište, - Dimenzije 163.4mm × 69.7mm × 70mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12V Dc ±30% /4.5W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	45.00	54.00
VND01024		<p><u>Dahua HAC-HFW1500D-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 3.6mm fiksni objektiv, - Vidni ugao 92° H, - Smart IC diode dometa cca. 80m, - Metalno kućište, - Dimenzije 241.8mm × 90.4mm × 90.4mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12V Dc/4.9W, - Pripadajuće dozne PFA130-E, PFA135, PFA152-E. 	77.00	92.40

VND01025		<p>Dahua HAC-HFW1500TH-I8-0360B</p> <ul style="list-style-type: none"> - 5MP bullet IC kamera, - 3.6mm F1.6 fiksni objektiv, - Vidni ugao 92° H, - Smart IC diode dometa cca. 80m, - Metalno i plastično kućište, - Dimenzije 240.7 mm × 90.7 mm × 90.4 mm, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/5.2W, - Pripadajuće dozne PFA130-E, PFA135, PFA152-E. 	57.00	68.40
VND01027		<p>Dahua HAC-HFW1500TLM-IL-A-0360B</p> <ul style="list-style-type: none"> - 5MP bullet sa hibridnim iluminatorima, - Objektiv 3.6mm, - Vidni ugao 92°, - IC i Bele LE diode dometa 40m, - Integriran mikrofoni, - Metalno i plastično kućište, - Dimenzije 198.4mm × 80.2mm × 76.2mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /4.5W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	56.00	67.20
VND01038		<p>Dahua HAC-HFW1509TLM-A-LED-0360B</p> <ul style="list-style-type: none"> - 5MP bullet sa Full Color kamera, - Objektiv 3.6mm, - Vidni ugao 88°H, - Bele LE diode dometa 40m, - Integriran mikrofoni, - Metalno i plastično kućište, - Dimenzije 198.4mm × 80.2mm × 76.2mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /9W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	81.00	97.20

VND01028		<p><u>Dahua HAC-HFW1509TLM-IL-A-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera, - Objektiv 3.6mm, - Vidni ugao 89°H, - Bele I IC LE diode dometa 40m, - Integrisan mikrofon, - Metalno i plastično kućište, - Dimenzije 198.4mm × 80.2mm × 76.2mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /5,7W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	85.00	102.00
VND01054		<p><u>Dahua HAC-HFW1500R-Z-IRE6-A-2712</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera, - 2.7~12mm F1.6 motorizovani zum , - Podesivi vidni ugao 34°~107° H, - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofon, - Starlight - Metalno kućište, - Dimenzije 209.9mm × 90.4mm × 90.4mm, - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Napajanje 12VDC ±30% /9,8W, - Pripadajuće dozne PFA13G, PFA152-E, PFA130-E. 	98.00	117.60
VND01055		<p><u>HAC-HFW1509T-A-LED-0360B</u></p> <ul style="list-style-type: none"> - 5MP bullet kamera, - Objektiv 3.6mm, - Vidni ugao 88°H, - Bele LE diode dometa cca. 20m, - Integrisan mikrofon, - Metalno kućište, - WDR 120 dB - Dimenzije 174.5mm × 72.3mm × 70.6mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /5,7W, - Pripadajuće dozne PFA134, PFA152-E, PFA130-E. 	85.00	102.00

VND01037		<p>Dahua HAC-HFW2501TU-A-0360B</p> <ul style="list-style-type: none"> - 5MP bullet kamera, - Objektiv 3.6mm, - Vidni ugao 92°H, - Pro serija, - Smart IC LE diode dometa cca. 80m, - Integrisan mikrofon, - Starlight, - WDR 120 dB, - Metalno kućište, - Dimenzije 244.1mm × 90.4mm × 90.4 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /6,8W, - Pripadajuće dozne PFA135, PFA152-E, PFA130-E. 	100.00	120.00
VND01056		<p>Dahua HAC-ME1509TH-A-PV-0360B</p> <ul style="list-style-type: none"> - 5MP Bullet kamera, - Fiksni objektiv 3.6 mm F1.0 , - Vidni ugao 89°H, - Bele IC LE diode dometa cca. 40m, - Integrisan mikrofon, - Alarmni izlaz, - Alarm crveno-plavo svetlo sirena 110 db, - 120 dB true WDR, 3D NR, - Metalno i plasticno kućište, - Dimenzije 240.7mm × Ø90.7mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30% /10.5W, - Pripadajuće dozne PFA130-E, PFA152-E. 	124.00	148.80
VND01008		<p>Dahua HAC-HDW1500CLQ-IL-A-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele LE diode dometa cca. 20m, - Integrisan mikrofon, - Plastično kućište, - Dimenzije 97.1 mm × 93.8 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+55°C, - Napajanje 12VDC ±30% /4,5W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 	47.00	56.40



VND01009		<p>Dahua HAC-HDW1500T-IL-A-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele LE diode dometa cca. 40m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije $\phi 106.0$ mm \times 93.6 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /4,5W, - Pripadajuće dozne PFA130, PFA152-E, PFA204W. 	55.00	66.00
VND01036		<p>Dahua HAC-HDW1500T-Z-A-2712</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Motorizovani objektiv 2.7~12mm F1.6 - Podesivi vidni ugao 34°~107°H, - Starlight - Smart IC LE diode dometa cca. 60m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije $\phi 122$mm \times 104.8mm - IP67 sertifikovana, - Radna temperatura -30°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /6.6W - Pripadajuće dozne PFA130, PFA152-E, PFA137. 	107.00	128.40
VND01040		<p>Dahua HAC-HDW1500TLMQ-IL-A-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele I IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Plastično i metalno kućište, - Dimenzije $\phi 109.9$ mm \times 88.1 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /3.1W, - Pripadajuće dozne PFA13G, PFA152-E, PFA150, PFA205W-E. 	48.00	57.60



VND01011		<p>Dahua HAC-HDW1500TRQ-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 111°H, - IC LE diode dometa cca. 25m, - Starlight - Plastično kućište, - Dimenzije $\Phi 97.1 \text{ mm} \times 93.0 \text{ mm}$, - IP50 sertifikovana, - Radna temperatura $-40^{\circ}\text{C} \sim +50^{\circ}\text{C}$, - Napajanje 12VDC $\pm 30\%$ /3.0W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 	40.00	48.00
VND01035		<p>Dahua HAC-HDW1509T-A-LED-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.0, - Vidni ugao 112°H, - Bele LE diode dometa cca. 40m, - Integrisan mikrofon, - 120 dB true WDR, 3D NR - Metalno kućište, - Dimenzije $\phi 106.0 \text{ mm} \times 93.6 \text{ mm}$ - IP67 sertifikovana, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - Napajanje 12VDC $\pm 30\%$ /6.4W - Pripadajuće dozne PFA130, PFA152-E, PFA139. 	85.00	102.00
VND01010		<p>Dahua HAC-HDW1500TLM-IL-A-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.6 , - Vidni ugao 106°H, - Bele I IC LE diode dometa cca. 20m, - Integrisan mikrofon, - Metalno kućište, - Dimenzije $\phi 94.0 \text{ mm} \times 85.7 \text{ mm}$ - IP67 sertifikovana, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - Napajanje 12VDC $\pm 30\%$ /3.1W, - Pripadajuće dozne PFA13-A, PFA152-E, PFA205W-E. 	49.00	58.80



VND01029		<p>Dahua HAC-ME1509TQ-A-PV-0280B</p> <ul style="list-style-type: none"> - 5MP dom kamera, - Fiksni objektiv 2.8mm F1.0 , - Vidni ugao 111°H, - Bele I C L E diode dometa cca. 40m, - Integrisan mikrofon, - Alarmni izlaz, - Alarm crveno-plavo svetlo, sirena 110 db, - Metalno i plasticno kućište, - Dimenzije $\Phi 109.9$ mm \times 100.9 mm, - IP67 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /10.5W, - Pripadajuće dozne PFA13G, PFA152-E, PFA205W-E. 	118.00	141.60
VND01049		<p>HAC-HDBW1500E-0280B-S2</p> <ul style="list-style-type: none"> - 5MP antivandal dom kamera, - Objektiv 2.8mm, - Vidni ugao 111°H, - Dometa cca. 30m, - Metalno kućište, - Dimenzije $\phi 109.9$ mm \times 81.0 mm, - IP67, IK10 sertifikovana, - Radna temperatura -40°C~+60°C, - Napajanje 12VDc $\pm 30\%$ /3,5W, - Pripadajuće dozne PFA136, PFB203W, PFA152-E. 	74.00	88.80



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
KAMERE HDCVI 8MPX				
VND01057		<p><u>Dahua HAC-HFW180TH-I8-0360B</u></p> <ul style="list-style-type: none"> - 8MP bullet IC kamera, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 87° H, - Smart IC LE diode dometa cca. 80m, - Metalno i plastično kućište, - Dimenzije 240.7 mm × 90.7 mm × 90.4 mm, - Radna temperatura -40°C~+60°C, - Napajanje 12VDC ±30%/6W, - Pripadajuće dozne PFA130-E, PFA152. 	80.00	96.00
VND01058		<p><u>Dahua HAC-HFW180TL-A-0360B</u></p> <ul style="list-style-type: none"> - 8MP bullet IC kamera, - 3.6mm F2.0 fiksni objektiv, - Vidni ugao 87° H, - Smart IC LE diode dometa cca. 80m, - Integriran mikrofoni, - Metalno i plastično kućište, - Dimenzije 198.9mm×80.2mm×76.2mm, - Radna temperatura -40°C~+60°C, - IP67 Sertifikovan, - Napajanje 12VDC ±30%/6W, - Pripadajuće dozne PFA134, PFA152. 	72.00	86.40
VND01039		<p><u>Dahua HAC-HDW1801TLM-IL-A-0280B</u></p> <ul style="list-style-type: none"> - 8MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 106° H, - Bele i IC LE diode dometa cca. 20m, - Integriran mikrofoni, - 120 dB true WDR, 3D NR, - Metalno kućište, - Dimenzije φ94.0 mm × 85.7 mm, - Radna temperatura -40°C~+60°C, - IP67 Sertifikovan, - Napajanje 12VDC ±30%/4.2W, - Pripadajuće dozne PFA13-A, PFA152, PFB205-W. 	98.00	117.60



VND01059		<p>Dahua HAC-HDW1801T-IL-A-0280B</p> <ul style="list-style-type: none"> - 8MP dom kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 106° H, - Bele i IC LE diode dometa cca. 40m, - Integrisan mikrofon, - 120 dB true WDR, 3D NR, - Metalno kućište, - Dimenzije $\phi 106.0$ mm \times 99.2 mm - Radna temperatura -40°C~+60°C, - IP67 Sertifikovan, - Napajanje 12VDC \pm30%/5.7W, - Pripadajuće dozne PFA130-E, PFA152, PFB204W. 	100.00	120.00
----------	---	---	--------	--------



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
DIGITALNI SNIMAČI				
VND03001		<p><u>Dahua XVR1B04-I</u></p> <ul style="list-style-type: none"> - 4+1 kanalni DVR - SMD+ detekcija pokreta na do 4 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Podržava 1 dodatnu IP kameru rezolucija do 2MP, ili do 5 IP kamera sa konvertovanjem anlognih u IP kanale, (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima) - Rezolucija snimanja po kameri 1080N/720P/960H/D1/CIF, - Rezolucija prikaza 1280×720 do 1920×1080 - 1 SATA port - HDD do 6TB, - Dimenzije 1U, 198mm × 202.9mm × 41.5mm 	75.00	90.00
VND03011		<p><u>Dahua XVR1B04-I (512G)</u></p> <ul style="list-style-type: none"> - 4+1 kanalni DVR, - Integrisan SSD od 512GB, - SMD+ detekcija pokreta na do 4 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Podržava 1 dodatnu IP kameru rezolucija do 2MP, ili do 5 IP kamera sa konvertovanjem anlognih u IP kanale, (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima) - Rezolucija snimanja po kameri 1080P/720P/960H/D1/CIF, - Rezolucija prikaza 1280×720 do 1920×1080 - 1 SATA port - HDD do 6TB, - Dimenzije 197.0mm × 203.4 mm × 41.5 mm 	150.00	180.00


VND03002		<p><u>Dahua XVR1B08-I</u></p> <ul style="list-style-type: none"> - 8+2 kanalni DVR - SMD+ detekcija pokreta na do 4 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Podržava 2 dodatne IP kamere rezolucija do 6MP ili do 10 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Rezolucija snimanja po kameri 1080N/720P/960H/D1/CIF, - Rezolucija prikaza 1280×720 do 1920×1080 - 1 SATA port - HDD do 6TB, - Dimenzije 197.0 mm × 202.9 mm × 41.5 mm, 	90.00	108.00
VND03003		<p><u>Dahua XVR1B16-I</u></p> <ul style="list-style-type: none"> - 16+2 kanalni DVR - SMD+ detekcija pokreta na do 8 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Podržava 2 dodatne IP kamere rezolucija do 6MP ili do 18 IP kamera sa konvertovanjem anlognih u IP kanale(uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Rezolucija snimanja po kameri 1080N/720P/960H/D1/CIF, - Rezolucija prikaza 1280×720 do 1920×1080 - 1 SATA port - HDD do 6TB, - Dimenzije 260.0 mm × 229.6 mm × 47.6 mm, 	160.00	192.00

VND030004		<p><u>Dahua XVR5104HS-I3</u></p> <ul style="list-style-type: none"> - 4+2 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 4 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri: 5M-N 4M-N /1080N /720P /960H /D1 /CIF - Rezolucija prikaza 1280×720 ili do 1920×1080 - 1 SATA port - do 6TB - Podržava do 2 dodatne IP kamera ili do 6 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	100.00	120.00
VND03005		<p><u>Dahua XVR5108HS-I3</u></p> <ul style="list-style-type: none"> - 8+4 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 8 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri: 5M-N 4M-N /1080N /720P /960H /D1 /CIF - Rezolucija prikaza 1280×720 ili do 1920×1080 - 1 SATA port - do 10TB - Podržava do 4 dodatne IP kamera ili do 12 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	180.00	216.00

VND03006		<p><u>Dahua XVR5116HS-I3</u></p> <ul style="list-style-type: none"> - 16+8 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 16 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri: 5M-N 4M-N /1080N /720P /960H /D1 /CIF - Rezolucija prikaza 1280×720 ili do 1920×1080 - 1 SATA port - do 16TB - Podržava do 8 dodatne IP kamera ili do 24 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	280.00	336.00
VND03007		<p><u>Dahua XVR5104HS-4KL-I3</u></p> <ul style="list-style-type: none"> - 4+4 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 4 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri:4K, 6MP, 5MP, 4MP/3MP, 4M-N/ 1080P/ 720P/ 960H/ D1 /CI - Rezolucija prikaza 1280×720 ili do 3840×2160 - 1 SATA port - do 10TB - Podržava do 4 dodatne IP kamera ili do 8 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	167.00	200.40

VND03008		<p><u>Dahua XVR5108HS-4KL-I3</u></p> <ul style="list-style-type: none"> - 8+8 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 8 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri:4K, 6MP, 5MP, 4MP/3MP, 4M-N/ 1080P/ 720P/ 960H/ D1 /CI - Rezolucija prikaza 1280×720 ili do 3840×2160 - 1 SATA port - do 16TB - Podržava do 8 dodatne IP kamera ili do 16 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	249.00	298.80
VND03009		<p><u>Dahua XVR5116H-4KL-I3</u></p> <ul style="list-style-type: none"> - 16+16 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 16 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri:4K, 6MP, 5MP, 4MP/3MP, 4M-N/ 1080P/ 720P/ 960H/ D1 /CI - Rezolucija prikaza 1280×720 ili do 3840×2160 - 1 SATA port - do 16TB - Podržava do 16 dodatne IP kamera ili do 32 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 260.0mm × 237.9 mm × 47.6mm 	533.00	639.60



VND03012		<p><u>Dahua XVR5216AN-I3</u></p> <ul style="list-style-type: none"> - 16+8 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 16 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri: 5M-N 4M-N /1080N /720P /960H /D1 /CIF - Rezolucija prikaza 1280×720 ili do 1920×1080 - 2 SATA port - svaki do 16TB - Podržava do 8 dodatne IP kamera ili do 24 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 375.0 mm × 289.6 mm × 53.0 mm. 	305.00	366.00
VND03010		<p><u>Dahua XVR5232AN-I3</u></p> <ul style="list-style-type: none"> - 32+16 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 32 kanala, - VGA I HDMI izlaz, - 1 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri: 5M-N 4M-N /1080N /720P /960H /D1 /CIF - Rezolucija prikaza 1280×720 ili do 1920×1080 - 2 SATA port - svaki do 16TB - Podržava do 16 dodatne IP kamera ili do 48 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 375.0 mm × 289.6 mm × 53.0 mm. 	595.00	714.00

VND03013		<p><u>Dahua XVR5216A-4KL-I3</u></p> <ul style="list-style-type: none"> - 16+16 kanalni DVR - AI - zaštita perimetra i prepoznavanja lica, - SMD+ detekcija pokreta na do 16 kanala, - VGA I HDMI izlaz, - 4 audio ulaz/1 izlaz, - Rezolucija snimanje po kameri:4K, 6MP, 5MP, 4MP/3MP, 4M-N/ 1080P/ 720P/ 960H/ D1 /CI - Rezolucija prikaza 1280×720 ili do 1920×1080 - 2 SATA port - svaki do 16TB - Podržava do 16 dodatne IP kamera ili do 32 IP kamera sa konvertovanjem anlognih u IP kanale (uključenje IP kanala onemogućava AI i SMD funkcije na svim kanalima), - Dimenzije 375.0 mm × 289.6 mm × 53.0 mm. 	620.00	744.00
----------	---	--	--------	--------







WIRELESS SERIES


Simple Connection, Flexible Usage



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
DAHUA CONSUMER KAMERE 2MPX				
<div style="background-color: green; color: white; padding: 5px; transform: rotate(-45deg); display: inline-block;">New</div> VND08001		<p><u>Dahua T2A-LED-0280B WIFI, RJ-45</u></p> <ul style="list-style-type: none"> - 2MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 98°, - LED diode 2kom do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista $\Phi 109.9$ mm \times 102.2 mm, - Napajanje: 12 VDC 	58.00	69.60
<div style="background-color: green; color: white; padding: 5px; transform: rotate(-45deg); display: inline-block;">New</div> VND08002		<p><u>Dahua F2C-LED-0280B WIFI, RJ-45</u></p> <ul style="list-style-type: none"> - 2MP bulit kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 98°, - LED diode 2kom do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 131.0 mm \times 78.4 mm \times 97.2 mm, - Napajanje: 12 VDC 	56.00	67.20

<p>New</p> <p>VND08012</p>		<p>Dahua C2K-P CUBE K1 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 2MP kamera, - 2,8mm, Fixni objektiv, - Vidni ugao H: 101°, - IC dioda 1kom , do 30m, - Dvosmerna komunikacija-integriran mikrofon i zvucnik, - Human Detection, Motion Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - Bluetooth upravljanje, - Radna temperatura -10 °C to +45 °C, - Dimenzije kucista 64 mm × 100 mm × 34 mm , - Napajanje: 12 VDC/PoE 	<p>102.00</p>	<p>122.40</p>
<p>DAHUA CONSUMER KAMERE 3 MPX</p>				
<p>New</p>		<p>Dahua C3A CUBE A1 WIFI, Tipe C</p> <ul style="list-style-type: none"> - 5MP PT kamera, - 2,8mm, Fixni objektiv, - Vidni ugao H: 99°, - IC dioda 1kom , do 10m, - Dvosmerna komunikacija-integriran mikrofon i zvucnik, - Human Detection, Motion Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - Bluetooth upravljanje, - Radna temperatura -10 °C to +45 °C, - Dimenzije kucista $\Phi 68$ mm × 31.9 mm × 119.2 mm - Napajanje: 12 VDC 	<p>42.00</p>	<p>50.40</p>
<p>New</p> <p>VND08010</p>		<p>Dahua H3B HERO B1 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 3MP PT kamera, - 2,8mm, Fixni objektiv, - Vidni ugao H: 99°, - IC dioda 1kom , do 10m, - Dvosmerna komunikacija-integriran mikrofon i zvucnik, - Human Detection, Motion Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - IP67, - Bluetooth upravljanje, - Pan: 0°-355°;Tilt: 0°-90°, - Rotacija slike horizontalno 350° , vertikalno -5~80, - Radna temperatura -10°C~+45°C, - Dimenzije kucista $\Phi 84$mm x 23.8mm, - Napajanje: 12 VDC, 1 A 	<p>48.00</p>	<p>57.60</p>

		<p>Dahua T3A-IL-0280 WIFI</p> <ul style="list-style-type: none"> - 3MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 103°, - 1 (IR LED); 1 (Warm light) do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista $\Phi 109.9$ mm \times 102.2 mm, - Napajanje: 12 VDC 	<p>59.00</p>	<p>70.80</p>
	<p>TIOC</p> 	<p>Dahua T3A-PV</p> <ul style="list-style-type: none"> - 3MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 103°, - 1 (IR LED); 1 (Warm light) do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 102.2 mm \times $\Phi 109.9$ mm - Napajanje: 12 VDC 	<p>98.00</p>	<p>117.60</p>
		<p>Dahua F3D-PV WIFI TIOC</p> <ul style="list-style-type: none"> - 3MP bulit kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 103°, - 1 (IR LED); 1 (Warm light) do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 158.3 mm \times $\Phi 76.8$ mm, - Napajanje: 12 VDC 	<p>86.00</p>	<p>103.20</p>

<p>New</p> <p>VND08009</p>		<p>Dahua P3B-PV PICOO B1 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 3MP PT kamera, - 3,6mm, Fixni objektiv, - Vidni ugao H: 78°, - Diode 4kom (2IC,2Led), do 30m, - Dvosmerna komunikacija-integriran mikrofon i zvučnik, - Motion Detection, Human Detection, Vehicle Detection, - Light Warning, Sound Warning, - Plastično kućište, - Micro SD kartica (max. 256GB), - IP67, - Pan: 0°–355°;Tilt: 0°–90°, - Rotacija slike 180°, - Radna temperatura –30 °C to +55 °C, - Dimenzije kućišta 116 mm × 138 mm × 139 mm , - Napajanje: 12 VDC, 1 A 	<p>94.00</p>	<p>112.80</p>
<p>New</p> <p>VND08005</p>		<p>Dahua P3AE-PV PICOO A2 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 3MP PT kamera, - 4mm, Fixni objektiv, - Vidni ugao H: 86.8°, - Diode 4kom (2IC,2Led) do 30m, - Dvosmerna komunikacija-integriran mikrofon i zvučnik, - Light Warning, Sound Warning, - SMD, Human Detection, Tripwire, Intrusion, - Plastično kućište, - Micro SD kartica (max. 256 GB), - IP67, - Pan: 0° to 345°;Tilt: 0° to +80°, - Rotacija slike 180°, - Radna temperatura –30 °C to +55 °C, - Dimenzije kućišta 140.5 mm × Φ111.0 mm, - Napajanje:12 VDC, 1 A ± 10% (included) - Nosac u kompletu 	<p>70.00</p>	<p>84.00</p>

<p>New</p>	<p>TiOC</p> 	<p>Dahua P3D-3F-PV</p> <ul style="list-style-type: none"> - 3+3MP PT kamera, - 2,8mm, Fixni objektiv, + 6mm PT - Vidni ugao H: 95°, PT H: 53° - Diode 2 (IR LED) do30m ; 2 (Warm light) do 20m - PT diode 2 (IR LED) do 50m; 2 (Warm light) do 40m - Dvosmerna komunikacija-integrisan mikrofon i zvcnik, - Light Warning, Sound Warning, - SMD, Human Detection, Tripwire, Intrusion, - Bluetooth pairing - Plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP66, - Pan: 0° to 352°,Tilt: 0° to 90°, - Rotacija slike 180°, - Radna temperatura –30 °C to +55 °C, - Dimenzije kucista 159.4 mm × 119.1 mm × 210 mm - Napajanje:12 VDC, - Nosac u kompletu 	<p>162.00</p>	<p>194.40</p>
DAHUA CONSUMER KAMERE 4 MPX				
<p>New</p> <p>VND08003</p>		<p>Dahua T4A-LED-0280 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 4MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 98°, - LED diode 2kom do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura –40 °C to +60 °C, - Dimenzije kucista Φ109.9 mm × 102.2 mm, - Napajanje: 12 VDC 	<p>60.00</p>	<p>72.00</p>

<p>New</p> <p>VND08004</p>		<p><u>Dahua F4C-LED-0280B WIFI, RJ-45</u></p> <ul style="list-style-type: none"> - 4MP bulit kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 98°, - LED diode 2kom do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 131.0 mm × 78.4 mm × 97.2 mm, - Napajanje: 12 VDC 	<p>58.00</p>	<p>69.60</p>
<p>New</p> <p>VND08011</p>		<p><u>Dahua C4K-P CUBE K1 WIFI, RJ-45</u></p> <p>+B16-4MP PT kamera,</p> <ul style="list-style-type: none"> - 2,8mm, Fixni objektiv, - Vidni ugao H: 92°, - IC dioda 1kom , do 30m, - Dvosmerna komunikacija-integrisan mikrofon i zvucnik, - Human Detection, Motion Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - Bluetooth upravljanje, - Radna temperatura -10 °C to +45 °C, - Dimenzije kucista 64 mm × 100 mm × 34 mm , - Napajanje: 12 VDC/PoE 	<p>110.00</p>	<p>132.00</p>
<p>New</p> <p>VND08006</p>		<p><u>Dahua H4C WIFI, RJ-45</u></p> <ul style="list-style-type: none"> - 4MP PT kamera, - 4mm, Fixni objektiv, - Vidni ugao H: 80.3°, - IC diode 1, do 15m, - Dvosmerna komunikacija-integrisan mikrofon i zvucnik, - Motion Detection, Human Detection, - Plasticno kuciste, - Micro SD kartica (max. 512 GB), - Pan: 0° to 325°, Tilt: -20° to +100°, - Rotacija slike 180°, - Radna temperatura -30 °C to +55 °C, - Dimenzije kucista 130.4mm×Φ95.5mm - Napajanje: 5 VDC, 1 A ± 10% (Type-C)(included) 	<p>58.00</p>	<p>69.60</p>

	 	<p>Dahua F4C-PV-0280 WIFI Tioc</p> <ul style="list-style-type: none"> - 4MP bulit kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 98°, - 2 (IR LED); 2 (Warm light) 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 131.0 mm × 78.4 mm × 97.2 mm, - Napajanje: 12 VDC 	88.00	105.60
DAHUA CONSUMER KAMERE 5 MPX				
 VND08014		<p>Dahua C5A CUBE A1 WIFI, Tipe C</p> <ul style="list-style-type: none"> - 5MP PT kamera, - 2,8mm, Fixni objektiv, - Vidni ugao H: 90°, - IC dioda 1kom , do 10m, - Dvosmerna komunikacija-integrisan mikrofon i zvcnik, - Human Detection, Motion Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - Bluetooth upravljanje, - Radna temperatura -10 °C to +45 °C, - Dimenzije kucista Φ68 mm × 31.9 mm × 119.2 mm - Napajanje: 12 VDC/PoE 	60.00	72.00
 VND08008		<p>Dahua H5B HERO B1 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 5MP PT kamera, - 2,8mm, Fixni objektiv, - Vidni ugao H: 99°, - IC dioda 1kom , do 10m, - Dvosmerna komunikacija-integrisan mikrofon i zvcnik, - Motion Detection, Human Detection, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - IP67, - Boluetooth upravljanje, - Pan: 0°-355°;Tilt: 0°-90°, - Rotacija slike horizontalno 350°, vertikalno -5~80, - Radna temperatura -10°C~+45°C, - Dimenzije kucista Φ84mm x 23.8mm, - Napajanje: 12 VDC, 1 A 	60.00	72.00




		<p><u>Dahua H5D-5F Wi-Fi Dual-Lens PT</u></p> <ul style="list-style-type: none"> - 5+5MP PT kamera, - 3,6mm Fixni objektiv, - Vidni ugao H: 86°, - 2 (IR LED); 1 (Warm light) do 30m, - Dvosmerna komunikacija-integrisan mikrofon i zvučnik, - Motion Detection, Human Detection, - Plasticno kuciste, - Bluetooth pairing - Micro SD kartica (max. 512 GB), - Pan: 0° to 349°,Tilt: -5° to 90°, - Rotacija slike 180°, - Radna temperatura -30 °C to +55 °C, - Dimenzije kucista $\Phi 80.9$ mm \times 125.7mm - Napajanje: 5 VDC, 	<p style="text-align: center;">94.00</p>	<p style="text-align: center;">112.80</p>
 <p style="text-align: center;">VND08007</p>		<p><u>Dahua P5B-PV PICOO B1 WIFI, RJ-45</u></p> <ul style="list-style-type: none"> - 5MP PT kamera, - 3,6mm, Fixni objektiv, - Vidni ugao H: 78°, - Diode 4kom (2IC,2Led), do 30m, - Dvosmerna komunikacija-integrisan mikrofon i zvučnik, - Motion Detection, Human Detection, Vehicle Detection, - Light Warning, Sound Warning, - Plasticno kuciste, - Micro SD kartica (max. 256GB), - IP67, - Pan: 0°-355°;Tilt: 0°-90°, - Rotacija slike 180°, - Radna temperatura -30 °C to +55 °C, - Dimenzije kucista 116 mm \times 138 mm \times 139 mm , - Napajanje: 12 VDC, 1 A 	<p style="text-align: center;">98.00</p>	<p style="text-align: center;">117.60</p>




<p>New</p> <p>VND08005</p>		<p>Dahua P5AE-PV PICOO A2 WIFI, RJ-45</p> <ul style="list-style-type: none"> - 5MP PT kamera, - 4mm, Fixni objektiv, - Vidni ugao H: 80,4°, - Diode 4kom (2IC,2Led) do 30m, - Dvosmerna komunikacija-integriran mikrofon i zvučnik, - SMD, Human Detection, Tripwire, Intrusion, linkage tracking, - Light Warning, Sound Warning, - Plastično kućište, - Micro SD kartica (max. 256 GB), - IP67, - Pan: 0° to 345°, Tilt: 0° to +80°, - Rotacija slike 180°, - Radna temperatura -30 °C to +55 °C, - Dimenzije kućišta 140.5 mm × Ø111.0 mm, - Napajanje: 12 VDC, 1 A ± 10% (included) - Nosac u kompletu 	<p>88.00</p>	<p>105.60</p>
<p>New</p>		<p>Dahua T5A-IL-0280 WIFI</p> <ul style="list-style-type: none"> - 5MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 108°, - 1 (IR LED); 1 (Warm light) do 30m, - Integriran mikrofon, - Human Detection, Motion Detection, - Metalno+plastično kućište, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kućišta Ø109.9 mm × 102.2 mm, - Napajanje: 12 VDC 	<p>80.00</p>	<p>96.00</p>
<p>New</p>	<p>TIOC</p> 	<p>Dahua T5A-PV</p> <ul style="list-style-type: none"> - 5MP dom kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 108°, - 1 (IR LED); 1 (Warm light) do 30m, - Integriran mikrofon, - Human Detection, Motion Detection, - Metalno+plastično kućište, - Micro SD kartica (max. 256 GB), - IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kućišta 102.2 mm × Ø109.9 mm - Napajanje: 12 VDC 	<p>112.00</p>	<p>134.40</p>



	<p style="text-align: center;">TiOC</p> 	<p><u>Dahua F5D-PV-0280 WIFI Tioc</u></p> <ul style="list-style-type: none"> - 5MP bulit kamera, - 2.8mm, Fixni objektiv, - Vidni ugao H: 104°, - 1 (IR LED); 1 (Warm light) do 30m, - Integrisan mikrofon, - Human Detection, Motion Detection, - Metalno+plasticno kuciste, - Micro SD kartica (max. 256 GB), IP67, - Radna temperatura -40 °C to +60 °C, - Dimenzije kucista 158.3 mm × Ø76.8 mm, - Napajanje: 12 VDC 	90.00	108.00
	<p style="text-align: center;">TiOC</p> 	<p><u>Dahua P5D-5F-PV</u></p> <ul style="list-style-type: none"> - 5+5MP PT kamera, - 2,8mm, Fixni objektiv, + 6mm PT - Vidni ugao H: 95°, PT H: 49° - Diode 2 (IR LED) do 30m ; 2 (Warm light) do 20m - PT diode 2 (IR LED) do 50m; 2 (Warm light) do 40m - Dvosmerna komunikacija-integrisan mikrofon i zvcnik, - Light Warning, Sound Warning, - SMD, Human Detection, Tripwire, Intrusion, - Bluetooth pairing - Plasticno kuciste, - Micro SD kartica (max. 256 GB), - IP66, - Pan: 0° to 352°,Tilt: 0° to 90°, - Rotacija slike 180°, - Radna temperatura -30 °C to +55 °C, - Dimenzije kucista 159.4 mm × 119.1 mm × 210 mm - Napajanje:12 VDC, - Nosac u kompletu 	180.00	216.00



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Dahua ECO serija (IP 2MPX)				
VND02029		<p><u>IPC-T1E20-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom IC kamera, - 2.8mm F2.0 fiksni objektiv, - Vidni ugao 115° H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 103.2 mm × Φ109.9 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 2 VDC/PoE, potrošnja do 4,8W, ±30%, - Pripadajuće dozne PFA13-A, PFA130-E, PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. 	60.00	72.00
VND02053		<p><u>IPC-B1E20-A-0360B</u></p> <ul style="list-style-type: none"> - 2MP bulit IC kamera, - 3.6mm F2.2 fiksni objektiv, - Vidni ugao 79° H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 2.8 W, ±30%, - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. 	60.00	72.00
VND02089		<p><u>IPC-B1E20-A-0280B</u></p> <ul style="list-style-type: none"> - 2MP bulit IC kamera, - 2.8mm F2.2 fiksni objektiv, - Vidni ugao 99° H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 2.8 W, ±30%, - Pripadajuće dozne PFA134, PFA130-E, PFA152-E. 	60.00	72.00

 VND02054		<p><u>IPC-B1E29-A-IL-0360B</u></p> <ul style="list-style-type: none"> - 2MP bulit 2 Multi-core (IC + warm) - 3,6mm F1,6 fiksni objektiv, - Vidni ugao 87° H, - Domet dioda IC do 30 m, Led do 15 m - Integrisan mikrofona, - Plastico kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.4 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA134,PFA130-E, PFA152-E. 	65.00	78.00
Dahua serija 1				
VND02005		<p><u>IPC-HDW1239V-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 104° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofona, - Metalno + Plastico kućište, - DWDR - Dimenzije 100.9 mm × Φ109.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do H.265 + intelligence on+ WDR + illuminator intensity): 4.5 W (12 VDC); 5.6 W (PoE) - Pripadajuće dozne PFA13G,,PFB205W, PFA152-E, PFA151,PFA106 i PFB220C. 	77.00	92.40

VND02008		<p><u>IPC-HFW1239TL1-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP bullet, 4 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 104° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Metalno + Plastično kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do H.265 + intelligence on+ WDR + illuminator intensity): 6.3 W (12 VDC); 7.8 W (PoE) - Pripadajuće dozne PFA134,,PFB205W, PFA152-E, 	75.00	90.00
VND02001		<p><u>HDBW1230DE-SW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Micro SD - Metalno kućište, - DWDR - Dimenzije Φ110.7 mm × 88.7 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.9 W (12 VDC) - Pripadajuće dozne PFA136,PFB203W, PFA152-E, PFA109 i PFB220C. 	103.00	123.60
VND02007		<p><u>IPC-HFW1230DS-SAW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70.0 mm × 128.6 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.1 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E, 	103.00	123.60

VND02047		<p><u>IPC-HDW1230DT-SAW-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Micro SD - Metalno + Plastico kućište, - DWDR - Dimenzije $\varnothing 109.9$ mm \times 102.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 6.1 W (12 VDC) - Pripadajuće dozne PFA13G, PFA134, PFA152-E, 	103.00	123.60
VND02004		<p><u>IPC-HFW1230DT-STW-0280</u></p> <ul style="list-style-type: none"> - 2MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD - Plastico kućište, metalni nosac, - DWDR - Dimenzije 166.2 mm \times 70.0 mm \times 128.6 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 2,2 W (12 VDC), potrošnja do 6.21 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E 		0.00
VND02002		<p><u>IPC-HDBW1230E-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 104° H, - Smart IC diode dometa cca. 30m, - Micro SD - Metalno kućište, - DWDR - Dimenzije $\varnothing 109.9$mm \times 81mm , - Radna temperatura -30°C~+60°C, - IP67 , IK10 sertifikovana, - Napajanje DC12V, PoE , potrošnja do <5W - Pripadajuće dozne PFA136,PFB203W, PFA152-E, 	80.00	96.00




VND02012		<p><u>IPC-HFW1230T-ZS-2812-S5</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 101°–33.5° H, - Smart IC diode dometa cca. 50m, - Integriran mikrofon, - Micro SD max. 256 GB, - Metalno kuciste, - DWDR - Dimenzije 244.1 mm × Ø90.4 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12V DC/PoE , potrošnja do 4.3 W (12V DC); 5.5 W (PoE) - Pripadajuće dozne: PFA130-E, PFA152-E 	154.00	184.80
Dahua serija 2				
VND02048		<p><u>IPC-HDW2249TM-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 107° H, - Smart IC LE diode dometa cca. 30m, - Integriran mikrofon, - Micro SD - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE , potrošnja do 3.8 W (12 VDC); 4.4 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C 	157.00	188.40

VND02011		<p><u>IPC-HFW2249S-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 107° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70 mm × 70mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.8 W (12 VDC); 4.4 W (PoE) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E 	157.00	188.40
VND02057		<p><u>IPC-HDBW2249E-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 2MP dom, 3 (IC LED); 4 (Warm light) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 105° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikroskop, - Micro SD max. 256 GB - Metalno kućište, plastican prsten, - DWDR - Dimenzije 81.0 mm × Φ109.9 mm , - Radna temperatura -30°C~+60°C, - IP67 , IK10, sertifikovana, - Napajanje DC12V, PoE , potrošnja do 6.2 W (12 VDC), 7.5 W (PoE) - Pripadajuće dozne PFA136, PFB203W, PFA152-E, PFA109 i PFB220C, 	157.00	188.40

<p>VND02058</p>		<p><u>IPC-HDW2241T-ZS-27135</u></p> <ul style="list-style-type: none"> - 2MP dom, 2 IC diode - 2.7 mm–13.5 mm F1.5 objektiv Moto-zoom, - Vidni ugao 108°–30° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE , potrošnja do 5.7 W (12 VDC); 6 W (PoE) - Pripadajuće dozne PFA130-E, PFB205W-E, PFA152-E, PFA106 i PFB220C 	<p>270.00</p>	<p>324.00</p>
-----------------	---	--	---------------	---------------


Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
Dahua ECO serija (IP 4MPX)				
 VND02016		<u>IPC-T1E40-A-0280B</u> - 4MP dom IC kamera, - 2.8mm F2.2 fiksni objektiv, - Vidni ugao H: 90°, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 103.2 mm × Φ109.9 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.0 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA13-G, PFA130-E, PFB205W, PFA152-E, PFA151, PFA109 i PFB220C.	69.00	82.80
 VND02030		<u>IPC-B1E40-A-0360B</u> - 4MP bulit IC kamera, - 3.6mm F2.2 fiksni objektiv, - Vidni ugao 76°H, - Smart IC diode dometa cca. 30m, - Integrisan mikroskop, - Plastično kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm, - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 3.0 W (12 VDC); 4.2 W (PoE) - Pripadajuće dozne PFA134, PFA130-E, PFA152-E.	69.00	82.80

 VND02055		<p><u>IPC-B1E49-A-IL-0360B</u></p> <ul style="list-style-type: none"> - 4MP bulit 2 Multi-core (IC + warm) - 3,6mm F1,6 fiksni objektiv, - Vidni ugao 78° H, - Domet dioda IC do 30 m, Led do 15 m - Integrisan mikrofon, - Plastico kućište, - Dimenzije 198.9 mm × 80.2 mm × 76.2 mm - Radna temperatura -40°C~+50°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE , potrošnja do 3.3 W (12 VDC); 4.25 W (PoE) - Pripadajuće dozne PFA134,PFA130-E, PFA152-E. 	88.00	105.60
Dahua serija 1				
VND02052		<p><u>IPC-HDW1439V-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plastico kućište, - DWDR - Dimenzije 100.9 mm × Φ109.9 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 4.6 W (12 VDC); 5.7 W (PoE) - Pripadajuće dozne PFA13G,,PFB205W, PFA152-E, PFA151, PFA106 i PFB220C. 	96.00	115.20
VND02013		<p><u>IPC-HFW1439TL1-A-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP bullit, 4 Multi-core (IC + warm) - 2.8mm F1,6 fiksni objektiv, - Vidni ugao 94° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Metalno + Plastico kućište, - DWDR - Dimenzije 197.9 mm × 80.2 mm × 76.2 mm , - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do: 6.4 W (12 VDC); 7.7 W (PoE) - Pripadajuće dozne PFA134, PFB205W, PFA152-E. 	96.00	115.20



VND02003		<p><u>IPC-HDBW1430DE-SW-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 3 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije $\Phi 110.7 \text{ mm} \times 88.7 \text{ mm}$, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67, IK10 sertifikovana, - Napajanje 12 VDC, potrošnja do 4.9 W (12 VDC) - Pripadajuće dozne PFA136,PFB203W, PFA152-E, PFA109 i PFB220C. 	119.00	142.80
VND02009		<p><u>IPC-HFW1430DS-SAW-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 100° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije $166.2 \text{ mm} \times 70.0 \text{ mm} \times 128.6 \text{ mm}$, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.1 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E. 	119.00	142.80
VND02051		<p><u>IPC-HDW1430DT-SAW-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Micro SD max 256GB - Metalno + Plastico kućište, - DWDR - Dimenzije $\Phi 109.9 \text{ mm} \times 102.2 \text{ mm}$, - Radna temperatura $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$, - IP67 sertifikovana, - Napajanje 2 W (12 VDC), potrošnja do 4.2 W (12 VDC) - Pripadajuće dozne PFA13G, PFA130-E, PFA152-E, PFA109+PFB220C 	120.00	144.00



VND02009		<p><u>IPC-HFW1430DS-SAW-0280</u></p> <ul style="list-style-type: none"> - 4MP dom, 1 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 90° H, - Smart IC diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max.256 GB - Plasticno kućište, metalni nosac, - DWDR - Dimenzije 180 mm × 83.3 mm × 114.8 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC, potrošnja do 6.1 W (12 VDC) - Pripadajuće dozne PFA134,PFA152-E 	119.00	142.80
VND02056		<p><u>IPC-HDW1431S-S-0280B-S4</u></p> <ul style="list-style-type: none"> - 4MP dom, 12 IC kamera - 2.8mm F2,0 fiksni objektiv, - Vidni ugao 104° H, - Smart IC diode dometa cca. 30m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije Φ108mm×84.9mm(- Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE, potrošnja do 5.5W - Pripadajuće dozne PFA130-E,PFA152-E, PFB203W 	104.00	124.80
VND02044		<p><u>IPC-HDW1431T-ZS-2812-S4</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 98°–31° H, - Smart IC diode dometa cca. 50m, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm , - Radna temperatura -30°C~+60°C, - IP67 sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.9W - Pripadajuće dozne PFA133-E, PFB203W, PFA152-E, PFA106+PFB220C 	190.00	228.00



VND02040		<p><u>IPC-HFW1431T-ZS-2812-S4</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 IC kamera - 2.8 mm–12 mm F1.7 moto-zoom, - Vidni ugao 98° - 31° H, - Smart IC diode dometa cca. 50m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kuciste, - DWDR - Dimenzije 244.1mm × Φ90.4 mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12V DC/PoE, potrošnja do 7.4W - Pripadajuće dozne: PFA130-E, PFA152-E 	190.00	228.00
Dahua serija 2				
VND02039		<p><u>IPC-HDW2449TM-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C 	178.00	213.60
VND02062		<p><u>IPC-HDW2449TM-S-IL-0280B BLACK</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofoni, - Micro SD max. 256 GB, - Metalno kućište, plastican prsten, - DWDR - Dimenzije 99.1 mm × Φ121.9 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFB203W, PFA152-E, PFA109 i PFB220C 	178.00	213.60



VND02034		<p><u>IPC-HFW2449S-S-IL-0280B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.8mm F1.6 fiksni objektiv, - Vidni ugao 95° H, - Smart IC LE diode dometa cca. 30m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 166.2 mm × 70 mm × 70mm - Radna temperatura -40°C~+60°C, - IP67 sertifikovana, - Napajanje 12 VDC/PoE, potrošnja do 4.4 W (12 VDC); 5.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA134, PFA152-E 	179.00	214.80
VND02019		<p><u>IPC-HFW2449T-AS-IL-0360B</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); 2 (Warm light) - 3,6 mm F1.6 fiksni objektiv, - Vidni ugao 84° H, - Smart IC LE diode dometa cca. 60m, cca 50 m (Warm light) - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 	194.00	232.80



VND02066		<p><u>IPC-HFW2449T-AS-IL-0360B BLACK</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); 2 (Warm light) - 3,6 mm F1.6 fiksni objektiv, - Vidni ugao 84° H, - Smart IC LE diode dometa cca. 60m, cca 50 m (Warm light) - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 238.5 mm × 90.7 mm × 90.7 mm , - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.2 W (PoE) - Pripadajuće dozne PFA130-E, PFA152-E. 	194.00	232.80
		<p><u>IPC-HDW2441T-ZS-27135</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); - 2.7 mm–13.5 mm F1.5 moto zoom objektiv, - Vidni ugao 104°–29° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofoni, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.1 W (12 VDC); 7.3 W (PoE) - Pripadajuće dozne PFA130, PFB205W, PFA152-E, PFA106 i PFB220C. 	270.00	324.00



		<p><u>IPC-HDBW2449R-ZAS</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 (IC LED); 4 (Warm light) - 2.7 mm–13.5 mm F1.5 motozoom objektiv, - Vidni ugao 104°–29° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište - DWDR - Dimenzije 93.4 mm × Φ122 mm, - Radna temperatura -30°C~+60°C, - IP67 , IK10, sertifikovana, - Napajanje DC12V, PoE, potrošnja do 6.5 W (12 VDC); 7.7 W (PoE) - Pripadajuće dozne PFA137, PFB203W, PFA152-E, PFA109 i PFB220C. 	290.00	348.00
VND02037		<p><u>IPC-HDW2449T-ZS-IL-27135</u></p> <ul style="list-style-type: none"> - 4MP dom, 2 Multi-core (IC + warm) - 2.7 mm–13.5 mm F1.5 moto zoom objektiv, - Vidni ugao 97°–28° H, - Smart IC LE diode dometa cca. 40m, - Integrisan mikrofon, - Micro SD max. 256 GB - Metalno kućište, - DWDR - Dimenzije 108.3 mm × Φ122.0 mm, - Radna temperatura -30°C~+60°C, - IP67 , sertifikovana, - Napajanje DC12V, PoE, potrošnja do 7.8 W (12 VDC), 9.3 W (PoE) - Pripadajuće dozne PFA130, PFB205W, PFA152-E, PFA106 i PFB220C. 	290.00	348.00



Šifra	Slika	Opis	VP bez PDV-a	MP sa PDV-om
MREŽNI SNIMAČI				
VND04004		<p><u>Dahua NVR1104HS-W-S2-CE</u></p> <ul style="list-style-type: none"> - 4 kanalni NVR WI-FI - Rezolucija 6 MP; 5 MP; 4 MP; 3 MP; 2 MP; 720p; D1 - 4ch 1080P real-time dekodiranje, maks. dekodiranje: 1ch@6MP, 2ch@4MP, 4ch@1080P - 1 x RCA In, 1 x RCA Out, 1 x Mrežni Port, HDMI i VGA Port - 1 x SATA Port (1 HDD do 16TB) - Automatsko uparivanje sa IPC kamerama u roku od 120 sekundi nakon pokretanja u uslovima bez smetnji, - Dimenzije 260.3mm x 247.3mm x 44.7mm 	124.00	148.80
VND04016		<p><u>Dahua NVR2104HS-4KS3</u></p> <ul style="list-style-type: none"> - 4 kanalni NVR, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1 kanal 12Mp @30 fps, 1 kanal 8 Mp @30 fps, 2 kanala 6Mp @30fps, 2 kanala 5Mp @30fps, 3 kanala 4Mp @ 30fps, 6 kanala 1080P @30fps, - Kapacitet dekodiranja AI uključen: 1 kanal 8Mp @30 fps, 1 kanal 6 Mp @30 fps, 1 kanal 5 Mp @30 fps, 2 kanala 4Mp @30fps, 4 kanala 1080P @30fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm x 232.5 mm x 47.6 mm 	118.00	141.60



VND04029		<p><u>Dahua NVR2104HS-P-4KS3</u></p> <ul style="list-style-type: none"> - 4 kanalni NVR sa 4 PoE porta, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; - Kapacitet dekodiranja AI isključen: 1 kanal 12Mp @30 fps, 1 kanal 8 Mp @30 fps, 2 kanala 6Mp @30fps, 2 kanala 5Mp @30fps, 3 kanala 4Mp @ 30fps, 6 kanala 1080P @30fps, - Kapacitet dekodiranja AI uključen: 1 kanal 8Mp @30 fps, 1 kanal 6 Mp @30 fps, 1 kanal 5 Mp @30 fps, 2 kanala 4Mp @30fps, 4 kanala 1080P @30fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm 	177.00	212.40
VND04017		<p><u>Dahua NVR2108HS-4KS3</u></p> <ul style="list-style-type: none"> - 8 kanalni NVR, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 6 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 6-kanala 1080p@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 8 MP@30 fps; 1-kanal 6 MP@30 fps; 1 kanal 5 MP@30 fps; 2-kanala 4 MP@30 fps; 4-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm 	136.00	163.20



VND04030		<p><u>Dahua NVR2108HS-P-4KS3</u></p> <ul style="list-style-type: none"> - 8 kanalni NVR sa 8 PoE porta, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 6 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 6-kanala 1080p@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 8 MP@30 fps; 1-kanal 6 MP@30 fps; 1 kanal 5 MP@30 fps; 2-kanala 4 MP@30 fps; 4-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm 	244.00	292.80
VND04002		<p><u>Dahua NVR4104HS-4KS3</u></p> <ul style="list-style-type: none"> - 4 kanalni NVR, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	143.00	171.60



VND04018		<p><u>Dahua NVR4104-EI</u></p> <ul style="list-style-type: none"> - 4 kanalni AL NVR, - AI - zaštita perimetra, detekcija i prepoznavanje lica, - Rezolucije snimanja 16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF, - Kapacitet dekodiranja AI isključen: 2-kanala 16 MP@30 fps; 2-kanala 12 MP@30 fps; 4-kanala 8 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 16 MP@30 fps; 2-kanala 12 MP@30 fps; 3-kanala 8 MP@30 fps; 3-kanala 6 MP@30 fps; 4-kanala 5 MP@30 fp, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 16TB, - Dimenzije 204.6mm × 206.4mm × 45.6mm. 	173.00	207.60
VND04014		<p><u>Dahua NVR4104HS-EI</u></p> <ul style="list-style-type: none"> - 4 kanalni AL NVR, - AI - zaštita perimetra, detekcija i prepoznavanje lica, - Rezolucije snimanja 16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF, - Kapacitet dekodiranja AI isključen: 2-kanala 16 MP@30 fps; 2-kanala 12 MP@30 fps; 4-kanala 8 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 16 MP@30 fps; 2-kanala 12 MP@30 fps; 3-kanala 8 MP@30 fps; 3-kanala 6 MP@30 fps; 4-kanala 5 MP@30 fp, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 16TB, - Dimenzije 260 mm × 232.7 mm × 47.6 mm. 	199.00	238.80

VND04008		<p><u>Dahua NVR4104HS-P-4KS3</u></p> <ul style="list-style-type: none"> - 4 kanalni POE NVR sa 4 portnim PoE switchem, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	194.00	232.80
VND04007		<p><u>Dahua NVR4108HS-4KS3</u></p> <ul style="list-style-type: none"> - 8 kanalni NVR, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps , - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-channel 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	165.00	198.00


VND04019		<p>Dahua NVR4108HS-8P-4KS3</p> <ul style="list-style-type: none"> - 8 kanalni POE NVR sa 8 portnim Poe switchem, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-channel 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	262.00	314.40
VND04011		<p>Dahua NVR4208-4KS3</p> <ul style="list-style-type: none"> - 8 kanalni NVR, - Rezolucije snimanja 12Mp; 8Mp; 6Mp; 5MP; 4MP; 3MP; 1080P; 720p; 960P; D1; CIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps , - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-channel 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	211.00	253.20


VND04015		<p><u>Dahua NVR4208-EI</u></p> <ul style="list-style-type: none"> - 8 kanalni NVR, - Rezolucije snimanja 16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF - Kapacitet dekodiranja AI isključen: 2-kanala 16 MP@30 fps; 2-kanala 12 MP@30 fps; 4-kanala 8 MP@30 fps; 6-kanala 5 MP@30 fps; 8-channel 4 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 16 MP@30 fps; 2-kanala 12 MP@30 fps; 3-kanala 8 MP@30 fps; 4-channel 5 MP@30 fps; 6-channel 4 MP@30 fps; 8-channel 1080p@30 fps, - AI zaštita perimetra, brojanje ljudi, heat map - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 4 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	270.00	324.00
VND04023		<p><u>Dahua NVR4208-8P-4KS3</u></p> <ul style="list-style-type: none"> - 8 kanalni POE NVR sa 8 portnim Poe switchem, - Rezolucije snimanja 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF; QCIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - AI zaštita perimetra, brojanje ljudi, heat map - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 6 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 375.0 mm × 327.9 mm × 53.0 mm. 	335.00	402.00


VND04024		<p><u>Dahua NVR4208-8P-EI</u></p> <ul style="list-style-type: none"> - 8 kanalni POE AI NVR sa 8 portnim Poe switchem, - Rezolucije snimanja 16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF - Kapacitet dekodiranja AI isključen: 2-kanala 16 MP@30 fps; 2-kanala 12 MP@30 fps; 4-kanala 8 MP@30 fps; 4-kanala 6 MP@30 fps; 6-kanala 5 MP@30 fps; 8-kanala 4 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 16 MP@30 fps; 2-kanala 12 MP@30 fps; 3-kanala 8 MP@30 fps; 3-kanala 6 MP@30 fps; 4-kanala 5MP@30 fps; 6-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps, - AI zaštita perimetra, brojanje ljudi, heat map - HDMI i VGA izlaz, - Alarmni ulaz x4, izlaz x2 - SMD+ detekcija pokreta do 8 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 375 mm × 329.3 mm × 53.0 mm. 	425.00	510.00
VND04001		<p><u>Dahua NVR4116HS-4KS3</u></p> <ul style="list-style-type: none"> - 16 kanalni NVR, - Rezolucije snimanja 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF; QCIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps , - Kapacitet dekodiranja AI uključen:1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 6 kanala, - 1 SATA HDD do 20TB, - Dimenzije 260.0 mm × 232.5 mm × 47.6 mm. 	184.00	220.80


VND04012		<p><u>Dahua NVR4216-4KS3</u></p> <ul style="list-style-type: none"> - 16 kanalni NVR, - Rezolucije snimanja 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF; QCIF - Kapacitet dekodiranja AI isključen:1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps , - Kapacitet dekodiranja AI uključen:1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 6 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 375.0mm × 282.9mm × 53.0mm 	233.00	279.60
VND04020		<p><u>Dahua NVR4216-EI</u></p> <ul style="list-style-type: none"> - 16 kanalni NVR, - Rezolucije snimanja 16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF - Kapacitet dekodiranja AI isključen: 2-kanala 16 MP@30 fps; 2-kanala 12 MP@30 fps; 4-kanala 8 MP@30 fps; 4-kanala 6 MP@30 fps; 6-kanala 5 MP@30 fps; 8-kanala 4 MP@30 fps; 16-kanala 1080p@30 fps , - Kapacitet dekodiranja AI uključen:1-kanal 16 MP@30 fps; 2-kanala 12 MP@30 fps; 3-kanala 8 MP@30 fps; 3-kanala 6 MP@30 fps; 4-kanala 5 MP@30 fps; 6-kanala 4 MP@30 fps; 12-kanala 1080p@30 fps; 16-kanala 720p@30 fps, - AI zaštita perimetra, brojanje ljudi, heat map - HDMI i VGA izlaz, - SMD+ detekcija pokreta do 8 kanala, - 2 SATA HDD svaki do 16TB, - Dimenzije 375 mm × 284.3 mm × 53 mm 	300.00	360.00


VND04006		<p><u>Dahua NVR4232-4KS3</u></p> <ul style="list-style-type: none"> - 32 kanalni NVR, - Rezolucije snimanja 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF; QCIF - Kapacitet dekodiranja AI isključen: 1-kanal 12 MP@30 fps; 2-kanala 8 MP@30 fps; 3-kanala 5 MP@30 fps; 4-kanala 4 MP@30 fps; 8-kanala 1080p@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 12 MP@30 fps; 1-kanal 8 MP@30 fps; 2-kanala 5 MP@30 fps; 3-kanala 4 MP@30 fps; 7-kanala 1080p@30 fps, - HDMI i VGA izlaz, - Audio ulaz/izlaz - 4 alarmna ulaza /2 alarmna izlaza - AI - zaštita perimetra - AI detekcija i prepoznavanje lica (do 6 kanala - analitika sa kamera) - SMD+ detekcija pokreta do 6 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 375.0mm x 282.9mm x 53.0mm 	325.00	390.00
----------	---	---	--------	--------


VND04009		<p>Dahua NVR5208-8P-EI</p> <ul style="list-style-type: none"> - 8 kanalni POE AI NVR sa 8 portnim Poe switchem, - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps, - Kapacitet dekodiranja AI uključen: 1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps;6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps, - AI zaštita perimetra, brojanje ljudi, heat map, face detection and recognition, ANPR, stereo analysis, - 2 HDMI i 2 VGA izlaz, - Alarmni ulaz x4, izlaz x2 - SMD+ detekcija pokreta do 8 kanala, - 2 SATA HDD svaki do 20TB, - Dimenzije 375 mm × 329.3 mm × 53.0 mm. 	680.00	816.00
----------	---	--	--------	--------


VND04005		<p><u>Dahua NVR5216-EI</u></p> <ul style="list-style-type: none"> -16 kanalni NVR, - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 10-kanala 6 MP@30 fps; 12-kanala 5 MP@30 fps , - Kapacitet dekodiranja AI uključen:1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp, - AI zaštita perimetra, brojanje ljudi, heat map - HDMI i VGA izlaz, - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 16 kanala, - 2 SATA HDD svaki do 16TB, - AcuPick AI - kamera + snimač do 16 kanala - Dimenzije 375 mm × 284.3 mm × 53 mm 	515.00	618.00
----------	---	--	--------	--------

		<p>Dahua NVR5216-16P-EI</p> <ul style="list-style-type: none"> -16 kanalni NVR sa 16 portnim Poe Switchem, - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 10-kanala 6 MP@30 fps; 12-kanala 5 MP@30 fps; 16-kanala 4 MP@30 fps - Kapacitet dekodiranja AI uključen:1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp, - AI zaštita perimetra, detekcija lica, prepoznavanje lica - HDMI i VGA izlaz, - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 8 kanala, - 2 SATA HDD svaki do 20TB, - AcuPick AI - kamera + snimač do 16 kanala - Dimenzije 375.0 mm × 329.3 mm x 53.0 mm 	770.00	924.00
--	---	--	--------	--------

VND04003		<p>Dahua NVR5232-EI</p> <ul style="list-style-type: none"> - 32 kanalni NVR - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 10-kanala 6 MP@30 fps; 12-kanala 5 MP@30 fps; 16-kanala 4 MP@30 fps; 32-kanala 1080p@30 fps - Kapacitet dekodiranja AI uključen: 1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp; 24-kanala 1080p@30 fps - AI zaštita perimetra, prepoznavanje lica, detekcija lica - HDMI i VGA izlaz, - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 8 kanala, - 2 SATA HDD svaki do 20TB, - AcuPick AI - kamera + snimač do 32 kanala - Dimenzije 375.0 mm × 284.4 mm x 56.0mm 	569.00	682.80
----------	---	--	--------	--------

VND04022		<p><u>Dahua NVR5432-EI</u></p> <ul style="list-style-type: none"> - 32 kanalni NVR - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 10-kanala 6 MP@30 fps; 12-kanala 5 MP@30 fps; 16-kanala 4 MP@30 fps; 32-kanala 1080p@30 fps - Kapacitet dekodiranja AI uključen: 1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp; 24-kanala 1080p@30 fps - AI zaštita perimetra, detekcija lica, prepoznavanje lica - 2 HDMI i 2 VGA izlaza, 2 RJ45 - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 8 kanala, - 4 SATA HDD svaki do 20TB, - AcuPick AI - kamera + snimač do 32 kanala - Dimenzije 440.0 mm × 415.1 mm x 70.0 mm 	927.00	1112.40
----------	---	--	--------	---------

VND04013		<p><u>Dahua NVR5464-EI</u></p> <ul style="list-style-type: none"> - 64 kanalni NVR - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 10-kanala 6 MP@30 fps; 12-kanala 5 MP@30 fps; 16-kanala 4 MP@30 fps; 32-kanala 1080p@30 fps - Kapacitet dekodiranja AI uključen: 1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 6 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp; 24-kanala 1080p@30 fps - AI zaštita perimetra, detekcija lica, prepoznavanje lica - 2 HDMI i 2 VGA izlaza, 2 RJ45 - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 8 kanala, - 4 SATA HDD svaki do 20TB, - AcuPick AI - kamera + snimač do 32 kanala - Dimenzije 440.0 mm × 415.1 mm x 70.0 mm 	1053.00	1263.60
----------	---	--	---------	---------

<p>VND03015</p>		<p><u>Dahua NVR5864-EI</u></p> <ul style="list-style-type: none"> - 64 kanalni NVR - Rezolucije snimanja 32 MP;24 MP;16 MP;12 MP;8 MP;5 MP;4 MP;3 MP;1080p;720p;D1;CIF;QCIF - Kapacitet dekodiranja AI isključen: 2-kanala 32 MP@25 fps; 2-kanala 24 MP@25 fps; 4-kanala 16 MP@30 fps; 5-kanala 12 MP@30 fps; 8-kanala 8 MP@30 fps; 12-kanala 5 MP@30 fps; 16-kanala 4 MP@30 fps; 32-kanala 1080p@30 fps - Kapacitet dekodiranja AI uključen: 1-kanal 32 MP@25 fps; 1-kanal 24 MP@25 fps; 2-kanala 16 MP@30 fps; 4-kanala 12 MP@30 fps; 6-kanala 8 MP@30 fps; 8-kanala 5 MP@30 fps; 12-kanala 4 MP@30 fp; 24-kanala 1080p@30 fps - AI zaštita perimetra, detekcija lica, prepoznavanje lica - 2 HDMI i 2 VGA izlaza, 2 RJ45 - ANPR (do 8 kanala - analitika sa kamera), - SMD+ detekcija pokreta do 8 kanala, - 8 SATA HDD svaki do 20TB, - AcuPick AI - kamera + snimač do 32 kanala - Dimenzije 439.9 mm × 457.9 mm x 89.0 mm 	<p>NA UPIT</p>	
-----------------	---	---	----------------	--